

Lift systems

AMF-BRUNS LINEARLIFT AL1 SOLID

reddot design award winner 2013

The fully automatic lift for rear and side entry








AMF-BRUNS LINEARLIFT AL1 SOLID

The fully automatic lift for rear and side entry



Worldwide unique design due to the specially manufactured aluminium profile lifting arms.



Design meets lightweight! Newly developed aluminium arms make the AL1 the lightest lift on the market.



See-through platform design ensures excellent rear view.

SPECIFICATION

- » Patented, newly developed aluminium arms make the AL1 the lightest lift on the market
- » Unique design
- » Applicable for rear and side entry
- » LED flashing lights, optional LED platform lights
- » Choice of 3 standard platforms

- » See-through platform design ensures excellent rear view
- » 900 mm lifting height
- » Roll-off stop opens automatically when touching ground even on uneven surfaces
- » Bridge plate serves as automatic roll-off stop at the same time (patented)
- » Crash security bolts for more passive security
- » Powder Coated surface. KTL coated for additional protection against corrosion.
- » Compatible with EMC in accordance with the European legislation
- » Meets EN 1756, II requirements

TECHNICAL DATA

» SWL 400 kg

» Operation control Via four push buttons up/down, stow/deploy

» Unladen weight Between 120 kg and 130 kg, depending on platform size

» Features Manual pump, two hand rails, automatic flashing


warning lights

» Power 12 \

electro-hydraulic motor

» Optional Remote control on request

Type AL1 Solid 1380



	TYPE	AL1 1380	AL1 1130	AL1 1065
nneı	Width	1.290 mm	1.200 mm	1.120 mm
	Depth	350 mm	350 mm	350 mm
	Hight	1.500 mm	1.250 mm	1.185 mm
	Useable platform size			
	Width	920 mm	830 mm	750 mm
	Length	1.380 mm	1.130 mm	1.065 mm



AMF-Bruns GmbH & Co. KG | Hauptstraße 101 | D-26689 Apen Telefon +49 (0) 44 89 / 72 72 50 | Fax +49 (0) 44 89 / 62 45 hubmatik@amf-bruns.de



